

Datenblatt Video Prozessor



MUSICLAND
EVENTTECHNIK /// TON /// LICHT /// VIDEO ///

Inputs		
Nums / Type	3xComposite 1xS-Video 1xYPbPr 2xVGA (RGBHV) 1xHDMI (1.3a with HDCP) 1xDVI (HDMI) 1xEXT. (Extended)	
Video system	PAL / NTSC	
Composite Video Scope / Impedance	1V (p_p) / 75Ω	
S-video Scope / Impedance	Y : 1.0V (p_p) / 75Ω, C : 0.35V (p_p) / 75Ω	
VGA Format	PC (VESA)	≤2048x1152@60Hz
VGA Scope / Impedance	R、 G、 B = 0.7 V (p_p) / 75Ω	
DVI Format	SD / HD (CEA-861)	≤1920x1080@60Hz
	PC (VESA)	≤2048x1152@60Hz
HDMI 1.3 Format(HDCP)	SD / HD (CEA-861)	≤1920x1080@60Hz
	PC (VESA)	≤2048x1152@60Hz
YPbPr Format	SD / HD (CEA-861)	≤1920x1080@60Hz
YPbPr Scope / Impedance	Y= 1.0V (p_p) / 75Ω Pb= 0.35V (p_p) / 75Ω Pr= 0.35V (p_p) / 75Ω	
SDI format	SDI-SMPTE 259M-C	576i @50Hz
		480i @60Hz
HD-SDI 3G-SDI format	HDSDI-SMPTE 292M SMPTE 274M/296M SMPTE 424M/425M	≤1920 x 1080@50Hz / 60Hz
AUDIO Scope / Impedance	2.0Vp-p / 10KΩ	
Input Connectors	VGA : 15pin D_Sub(Female) DVI : 24+1 DVI_D YPbPr: BNCx3 Composite : BNC S-VIDEO : 4pin mini DIN(Female) SDI / HD-SDI / 3G-SDI : BNC	

Outputs	
Nums / Type	1xVGA (RGBHV) 2xDVI
VGA / DVI Format	1024x768@60Hz / 75Hz 1280x1024@60Hz / 75Hz 1600x1200@60Hz 1920x1080@50Hz / 60Hz 1366x768@60Hz 1440x900@60Hz 2048x1152@60Hz 2304x1152@60Hz 2560x816@60Hz
VGA Scope / Impedance	R、G、B = 0.7 V (p_p) / 75Ω
Output Connectors	VGA OUT : 15pin D_Sub(Female) DVI OUT1 : 24+5 DVI_I DVI OUT2 : 24+1 DVI_D
Others	
Control	Panel Button / Knob / RS232
Power	100-240VAC 35W 50 / 60Hz
Operating Temp	5-40 °C
Humidity	15-85%
Dimensions (Package)	145 mm (height) x370mm (width) x535mm (length)
Weight (G.W.)	5.0 Kg
Weight (N.W.)	3.2Kg